



# ROLLED ALUMINUM / STAINLESS STEEL JACKETING

Standard Metal Industries, LLC  
500 S. 9th Street  
Leighton, PA 18235  
(610) 377-5400 Phone  
(610) 377-9500 Fax  
service@smimetal.com

## DESCRIPTION

**SMI Aluminum Roll Jacketing** is manufactured from 3003 Alloy H-14 or 3105 Alloy in conformance with ASTM B-209 and ANSI H35-2. The 3003 alloy contains .12% Copper and 1.2% Manganese which allows for easy bending and shaping.

**SMI Stainless Steel Jacketing** is manufactured from T304, or T316 by special order; and conforms to ASTM A240. T304 contains 18-20% chromium and 8-10.5% nickel whereas T316 contains 16-18% chromium, 10-14% nickel and 2-3% molybdenum. SMI recommends T316 for more severe corrosive environments, such as low concentrations of sulfuric acid, or higher concentrations of acetic acid or seawater.


## BOTH PRODUCTS

All products generally come in a standard mill finish, but bright annealed is available by special order. The products are sold in rolls of 50' to 100' depending on thickness. Custom roll lengths are available on request. The product is available with polyethylene/kraft, PolySurlyn™, or no vapor retarder as per customer request.


## USES

SMI Aluminum and Stainless Steel Jackets are recommended to help protect insulated pipe and tank systems from mechanical damage and weather intrusion when installed in a properly designed system. Standard nominal thicknesses are .016", .020", .024", .032" and are available in three styles: Stucco Embossed (SE), 3/16" Corrugated (CO), and Smooth (SM). Please

### SE



### CO



### SM

